

Package: s20x (via r-universe)

September 13, 2024

Version 3.1-40

Date 2023-08-21

Title Functions for University of Auckland Course STATS 201/208 Data Analysis

Description A set of functions used in teaching STATS 201/208 Data Analysis at the University of Auckland. The functions are designed to make parts of R more accessible to a large undergraduate population who are mostly not statistics majors.

Depends R (>= 4.0.0)

Suggests emmeans

Encoding UTF-8

Imports stats, graphics, methods

License GPL-2 | file LICENSE

RoxygenNote 7.2.3

URL <https://github.com/STATS-UOA/s20x>

BugReports <https://github.com/STATS-UOA/s20x/issues>

Repository <https://stats-uoa.r-universe.dev>

RemoteUrl <https://github.com/stats-uoa/s20x>

RemoteRef HEAD

RemoteSha 547d2bf750af4b081b561220f98653efde5f588e

Contents

| | |
|-----------------------|---|
| airpass.df | 3 |
| apples.df | 3 |
| arousal.df | 4 |
| autocorPlot | 4 |
| beer.df | 5 |
| body.df | 5 |
| books.df | 6 |

| | |
|-----------------------------|----|
| boxqq | 6 |
| bursary.df | 7 |
| butterfat.df | 7 |
| camplake.df | 8 |
| chalk.df | 8 |
| ciReg | 9 |
| computer.df | 10 |
| cooks20x | 10 |
| course.df | 11 |
| course2way.df | 12 |
| crossFactors | 12 |
| crossstabs | 13 |
| diamonds.df | 14 |
| displayPairs | 14 |
| eovcheck | 16 |
| estimateContrasts | 17 |
| fire.df | 19 |
| freq1way | 19 |
| fruitfly.df | 21 |
| getVersion | 21 |
| house.df | 22 |
| incomes.df | 22 |
| interactionPlots | 22 |
| lakemary.df | 25 |
| larain.df | 25 |
| layout20x | 25 |
| levene.test | 26 |
| mazda.df | 27 |
| mening.df | 27 |
| mergers.df | 27 |
| modcheck | 28 |
| modelcheck | 29 |
| mozart.df | 30 |
| multipleComp | 30 |
| nail.df | 31 |
| normcheck | 31 |
| onewayPlot | 34 |
| oysters.df | 36 |
| pairs20x | 36 |
| peru.df | 37 |
| predict20x | 37 |
| predictCount | 39 |
| predictGLM | 40 |
| propstsd.new | 41 |
| rain.df | 41 |
| residPlot | 42 |
| rowdistr | 43 |
| rr | 44 |

| | |
|-------------------------|-----------|
| <i>airpass.df</i> | 3 |
| seeds.df | 44 |
| sheep.df | 45 |
| skewness | 45 |
| skulls.df | 46 |
| snapper.df | 46 |
| soyabean.df | 47 |
| stripqq | 47 |
| summary1way | 48 |
| summary2way | 49 |
| summaryStats | 51 |
| teach.df | 53 |
| technitron.df | 54 |
| thyroid.df | 54 |
| toothpaste.df | 55 |
| trendscatter | 55 |
| zoo.df | 57 |
| Index | 58 |

| | |
|-------------------|---|
| <i>airpass.df</i> | <i>International Airline Passengers</i> |
|-------------------|---|

Description

Number of international airline passengers (in thousands) recorded monthly from January 1949 to December 1960.

Format

A time series with 144 observations.

| | |
|------------------|--------------------|
| <i>apples.df</i> | <i>Apples Data</i> |
|------------------|--------------------|

Description

These data come from a classic long-term experiment conducted at the East Malling Research Station, Kent, which is the centre for research into apple growing in the U.K. Commercial apple trees consist of two parts grafted together. The lowest part, the *rootstock*, largely determines the size of the tree, while the upper part (the *scion*) determines the fruit characteristics. Rootstocks propagated by cuttings (i.e. asexually produced) were once thought to result in smaller trees than those propagated from seeds (i.e. sexually produced). This hypothesis was re-examined in an experiment begun in 1918. Several trees of each type of 16 types of rootstock were planted, all trees having the same scion. Rootstocks I-IX were asexually produced, while X-XVI were sexually produced. In the winter of 1933-4 a number of trees were removed to make room for more, and the data presented here consists of the above ground weights of 104 trees felled in this period. No trees of types VIII, XI or XIV were felled. The description is from Lee (*Lee, A.J. Data analysis. An introduction based on R. University of Auckland 1994*). The data are from Andrews and Herzberg (1985).

Format

The data consist of a data frame with 104 observations on 3 variables.

| | | | |
|------|------------|---------|--|
| [,1] | Rootstock | factor | levels (I, II, III, IV, IX, V, VI, VII, X, XII, XIII, XV, XVI) |
| [,2] | Weight | integer | . |
| [,3] | Propagated | factor | levels (cutting, seed) |

arousal.df

Changes in Pupil Size with Emotional Arousal

Description

Data from an experiment to measure the effect of different images on emotional arousal, by measuring changes in pupil diameter. The experiment used 20 males and 20 females. Images included a nude man, nude woman, infant, and a landscape.

Format

A data frame with 160 observations on 3 variables.

| | | | |
|------|---------|---------|--|
| [,1] | arousal | numeric | Change in the subject's pupil size |
| [,2] | gender | factor | Subject's gender (female, male) |
| [,3] | picture | factor | Picture shown to subject (infant, landscape, nude female, nude male) |

autocorPlot

Autocorrelation Plot

Description

Plots current vs lagged residuals along with quadrants dividing these residuals about the value zero.

Usage

```
autocorPlot(fit, main = "Current vs Lagged residuals", ...)
```

Arguments

| | |
|------|---|
| fit | output from the function 'lm()'. |
| main | the plot title. |
| ... | extra parameters to be passed to the plot function. |

Value

Plots current vs lagged residuals along with quadrants dividing these residuals about the value zero.

Note

autocor.plot is deprecated inline with our new policy of removing periods from function names.

Examples

```
data(airpass.df)
time = 1:144
airpass.fit = lm(passengers ~ time, data = airpass.df)
autocorPlot(airpass.fit)
```

 beer.df

US Beer Production

Description

Monthly United States beer production figures (in millions of 31-gallon barrels) for the period July 1970 to June 1978.

Format

A time series with 96 observations.

 body.df

Body Image and Ethnicity

Description

Data collected to examine how women from various ethnic groups rate their body image. All subjects were slightly underweight for their body size.

Format

A data frame with 246 observations on 8 variables.

| | | | |
|------|-----------|--------|---|
| [,1] | ethnicity | factor | Subject's ethnicity (Asian, Europn, Maori, Pacific) |
| [,2] | married | . | . |
| [,3] | bodyim | factor | Subject's rating of themselves (slight.uw, right, slight.ow, mod.ow, very.ow) |
| [,4] | sm.ever | . | . |
| [,5] | weight | . | . |
| [,6] | height | . | . |
| [,7] | age | . | . |
| [,8] | stressgp | . | . |

books.df

*Books Data***Description**

This data consists of 50 sentence lengths from each of 8 books. The books “Disclosure” and “Rising Sun” were written by Michael Crichton, whilst the others “Four Past Midnight”, “The Dark Half”, “Eye of the Dragon”, “The Shining”, “The Stand” and “The Tommy-Knockers” were written by Stephen King. The pages and sentences were chosen using a multistage design where the pages were selected at random, and then sentences within each page were selected at random. These data were collected by James Curran.

Format

The data frame consists of 400 observations on 2 variables.

```
[,1] length integer
[,2] book factor levels (4.Past.Mid, Dark.Half, Disclosure, Eye.Drag,
Rising.Sun, Shining, Stand, T.Knock)
```

boxqq

*Box plots and normal quantile-quantile plots***Description**

Draws boxplots and normal quantile-quantile plots of x for each value of the grouping variable g

Usage

```
boxqq(formula, ...)

## S3 method for class 'formula'
boxqq(formula, data = NULL, ...)
```

Arguments

`formula` A symbolic specification of the form $x \sim g$ can be given, indicating the observations in the vector x are to be grouped according to the levels of the factor g . NA's are allowed in the data.

`...` Arguments to be passed to methods, such as graphical parameters (see [par](#)).

`data` An optional data frame in which to evaluate the formula.

Value

Returns the plot.

Methods (by class)

- `boxqq(formula)`: Box plots and normal quantile-quantile plots

Note

This function is deprecated and will be removed in later versions of the package.

Examples

```
## Zoo data
data(zoo.df)
boxqq(attendance ~ day.type, data = zoo.df)
```

bursary.df

Bursary Results for Auckland Secondary Schools

Description

Data for the 2001 Bursary results for 75 secondary schools in the Auckland area. For each school the decile rating of the school is recorded along with the percentage of eligible students who gain a B Bursary or better.

Format

A data frame with 75 observations on 2 variables.

| | | | |
|------|-----------|---------|--|
| [,1] | decile | numeric | Decile rating of the school |
| [,2] | pass.rate | numeric | Percentage of eligible students who gained a 'B' Bursary or better |

butterfat.df

Butterfat Data

Description

This data gives the mean percentage of butterfat produced by different Canadian pure-bred diary cattle. There are five different breeds and two age groups, two years old and greater than five years old. For each combination of breed and age, there are measurements for 10 cows.

Format

A data frame with 100 observations on 3 variables.

| | | | |
|------|-----------|---------|--|
| [,1] | Butterfat | numeric | Mean percentage of butterfat per cow |
| [,2] | Breed | factor | Breed (ayrshire, canadian, guernesy, holst.fres, jersey) |
| [,3] | Age | factor | Age group (2yo, mature) |

Source

A Handbook of Small Data Sets

References

Hand, D.J., Daly, F., Lunn, A.D., McConway, K.J. and Ostrowski, E. (1994). *A Handbook of Small Data Sets*. Boca Raton, Florida: Chapman and Hall/CRC.

Sokal, R.R. and Rohlf, F.J. (1981). *Biometry*, 2nd edition. San Francisco: W.H. Freeman, 368.

| | |
|-------------|--|
| camplake.df | <i>Age and Length of Camp Lake Bluegills</i> |
|-------------|--|

Description

66 bluegills were captured from Camp Lake, Minnesota. For each bluegill we have the length of the fish, its age in years and its age in scale radius.

Format

A data frame with 66 observations on 3 variables.

| | | | |
|------|--------------|---------|---|
| [,1] | Age | numeric | Age of fish (years) |
| [,2] | Scale.Radius | numeric | Age of fish (radius of the key scale (mm/100)) |
| [,3] | Length | numeric | Length at capture (mm) |

| | |
|----------|-------------------|
| chalk.df | <i>Chalk Data</i> |
|----------|-------------------|

Description

These data involve 11 laboratories and 2 brands of chalk. The laboratories tested the density of the chalk. The main interest was whether the different laboratories yielded the same density for the two different types of chalk.

Format

A data frame with 66 observations on 3 variables.

| | | | |
|------|---------|---------|-------------------------------|
| [,1] | Density | numeric | Density of the chalk |
| [,2] | Lab | integer | Laboratory where testing done |
| [,3] | Chalk | factor | Chalk tested (A, B) |

ciReg

Confidence Intervals for Regression models

Description

Calculates and prints the confidence intervals for the fitted model.

Usage

```
ciReg(fit, conf.level = 0.95, print.out = TRUE)
```

Arguments

| | |
|------------|---|
| fit | an object of class <code>lm</code> , i.e. the output from <code>lm</code> . |
| conf.level | confidence level of the intervals. |
| print.out | if TRUE, print out the output on the screen. |

Value

The function returns a two-column matrix containing the upper and lower endpoints of the intervals.

See Also

[lm](#), [summary](#), [anova](#).

Examples

```
##Peruvian Indians data
data(peru.df)
fit=lm(BP ~ age + years + weight + height, data = peru.df)
ciReg(fit)
```

 computer.df

Computer Questionnaire

Description

Data from a test to see if a questionnaire was properly designed. The questionnaire measures managers' technical knowledge of computers. The test has 19 managers complete the questionnaire as well as rate their own technical expertise.

Format

A data frame with 19 observations on 2 variables.

| | | | |
|------|------------|----------------|--|
| [,1] | score | numeric | Questionnaire score |
| [,2] | selfassess | ordered factor | Self-assessed level of expertise (1 = low, 2 = medium, 3 = high) |

 cooks20x

Cook's distance plot

Description

Draws a Cook's distance plot.

Usage

```
cooks20x(
  x,
  main = "Cook's Distance plot",
  xlab = "observation number",
  ylab = "Cook's distance",
  line = c(0.5, 1.2, 2),
  cex.labels = 1,
  axisOpts = list(xAxis = TRUE, yAxisTight = FALSE),
  ...
)
```

Arguments

| | |
|------|--|
| x | an object of class <code>lm</code> , usually obtained by using the <code>lm</code> function. |
| main | the plot title |
| xlab | the x-axis title. |
| ylab | the y-axis title. |
| line | a vector of length 3 controlling the distances of the plot title, the x-axis title and the y-axis title from the axis in line units. |

cex.labels a factor controlling the font size of the labels on suspected high influence points.
 axisOpts a list of additional arguments that can be used to control the axes. At this point this list only contains one element xAxis which is logical. If xAxis == TRUE then the x-axis will be displayed, and clearly, if it is FALSE, then it will not.
 ... additional arguments are passed to plot and may provide some extra flexibility.

Value

Returns the plot and identifies the three highest Cook's values

Examples

```
# Peruvian Indians data
data(peru.df)
peru.fit = lm(BP ~ age + years + I(years^2) + weight + height, data = peru.df)
cooks20x(peru.fit)
```

 course.df

Stats 20x Summer School Data

Description

Data from a summer school Stats 20x course. Each observation represents a single student.

Format

A data frame with 146 observations on 15 variables.

| | | | |
|-------|-------------|---------|--|
| [,1] | Grade | factor | Final grade for the course (A, B, C, D) |
| [,2] | Pass | factor | Passed the course (No, Yes) |
| [,3] | Exam | numeric | Mark in the final exam |
| [,4] | Degree | factor | Degree enrolled in (BA, BCom, BSc, Other) |
| [,5] | Gender | factor | Gender (Female, Male) |
| [,6] | Attend | factor | Regularly attended class (No, Yes) |
| [,7] | Assign | numeric | Assignment mark |
| [,8] | Test | numeric | Test mark |
| [,9] | B | numeric | Mark for the short answer section of the exam |
| [,10] | C | numeric | Mark for the long answer section of the exam |
| [,11] | MC | numeric | Mark for the multiple choice section of the exam |
| [,12] | Colour | factor | Colour of the exam booklet (Blue, Green, Pink, Yellow) |
| [,13] | Stage1 | factor | Stage one grade (A, B, C) |
| [,14] | Years.Since | numeric | Number of years since doing Stage 1 |
| [,15] | Repeat | factor | Repeating the paper (No, Yes) |

| | |
|---------------|--|
| course2way.df | <i>Exam Mark, Gender and Attendance for Stats 20x Summer School Students</i> |
|---------------|--|

Description

Data from a summer school Stats 20x course. Each observation represents a single student. It is of interest to see if there is a relationship between a student's final examination mark and both their gender and whether they regularly attend lectures.

Format

A data frame with 40 observations on 3 variables.

| | | | |
|------|--------|---------|-------------------------------------|
| [,1] | Exam | numeric | Final exam mark (out of 100) |
| [,2] | Gender | factor | Gender (Female, Male) |
| [,2] | Attend | factor | Regularly attended or not (No, Yes) |

| | |
|--------------|------------------------|
| crossFactors | <i>Crossed Factors</i> |
|--------------|------------------------|

Description

Computes a factor that has a level for each combination of the factors 'fac1' and 'fac2'.

Usage

```
crossFactors(x, fac2 = NULL, ...)

## Default S3 method:
crossFactors(x, fac2 = NULL, ...)

## S3 method for class 'formula'
crossFactors(formula, fac2 = NULL, data = NULL, ...)
```

Arguments

| | |
|---------|---|
| x | the name of the first factor or a formula in the form ~ fac1 * fac2 |
| fac2 | the name of the second factor - ignored if x is a formula. |
| ... | Optional arguments |
| formula | a formula in the form ~ fac1 * fac2 |
| data | an optional data frame in which to evaluate the formula |

Value

Returns a vector containing the factor which represents the interaction of the given factors.

Methods (by class)

- `crossFactors(default)`: Crossed Factors
- `crossFactors(formula)`: Crossed Factors

Note

This function actually returns a factor now instead of a character string, so coercion into a factor is no longer necessary.

See Also

[factor](#).

Examples

```
## arousal data:
data(arousal.df)
gender.picture = crossFactors(arousal.df$gender, arousal.df$picture)
gender.picture

## arousal data:
data(arousal.df)
gender.picture = crossFactors(~ gender * picture, data = arousal.df)
gender.picture
```

crosstabs

Crosstabulation of two variables

Description

Produces a 2-way table of counts and the corresponding chi-square test of independence or homogeneity.

Usage

```
crosstabs(formula, data)
```

Arguments

| | |
|---------|--|
| formula | a symbolic description of the model to be fit: \sim fac1 + fac2; where fac1 and fac2 are vectors to be crosstabulated and treated internally as factors. |
| data | an optional data frame containing the variables in the model. |

Value

An invisible list containing the following components:

| | |
|-----------|---|
| row.props | a matrix of row proportions, i.e. cell counts divided by row marginals. |
| col.props | a matrix of column proportions, i.e. cell counts divided by column marginals. |
| Totals | a matrix containing the cell counts and the marginal totals. |

Note

This function is deprecated and will be removed in future versions of the package.

Examples

```
##body image data:
data(body.df)
crosstabs(~ ethnicity + married, body.df)
```

| | |
|-------------|---------------------------------------|
| diamonds.df | <i>Prices and Weights of Diamonds</i> |
|-------------|---------------------------------------|

Description

Prices of ladies' diamond rings from a Singaporean retailer and the weight of their diamond stones.

Format

A data frame with 48 observations on 2 variables.

| | | | |
|------|--------|---------|-----------------------------------|
| [,1] | price | numeric | Price of ring (Singapore dollars) |
| [,2] | weight | numeric | Weight of Diamond (carats) |

| | |
|--------------|---|
| displayPairs | <i>Display within-level pairwise comparisons for saturated two-way ANOVA model.</i> |
|--------------|---|

Description

Displays within-level pairwise comparisons from a two-way ANOVA with interactions. Note that this is just a display function: it ignores any cross-level pairs included in allpairs, even though these will have contributed to the computations for the Tukey adjustments. The purpose is just to organise the output from emmeans into a more convenient format.

Usage

```
displayPairs(allpairs, levels1, levels2, brief = TRUE, asDF = FALSE)
```

Arguments

| | |
|----------|---|
| allpairs | pairwise output from a command like pairs. See details for a longer explanation. |
| levels1 | a character string specifying which within-level comparisons from factor1 are wanted, and in which order. |
| levels2 | a character string specifying which within-level comparisons from factor2 are wanted, and in which order. |
| brief | either TRUE or FALSE. If TRUE then the information displayed will be more succinct. |
| asDF | either TRUE or FALSE specifying whether to return a data.frame of results or just to display the output. |

Details

allpairs is a pairwise output from a command like pairs(emmeans(fit, ~factor1 * factor2)). If allpairs is not already a data.frame it will be converted to a data.frame within this function. It must contain a column called contrast with text descriptions like 'lev1 lev2 - lev3 lev4' etc. levels1 and levels2 are character strings specifying which within-level comparisons are wanted, and in which order. They must match the order specified in emmeans, so if using emmeans(fit, ~factor1 * factor2) then levels1 must belong to factor1 and levels2 must belong to factor2. All this function does is to pick out the rows of allpairs with the requested contrasts, so if there are no contrasts of the requested format (e.g. because levels1 and levels2 have been switched) it will output a blank list. If brief = TRUE, columns labelled df, SE, and t.ratio or z.ratio will be removed for a more succinct display. If asDF = TRUE, the output is returned as a data-frame suitable for further manipulation, whereas if asDF = FALSE it is returned as a list for display only.

Author(s)

Rachel Fewster

Examples

```
## Fit a two-way ANOVA to the arousal data in arousal.df.
## The factors are gender (female, male) and picture shown to
## subject (infant, landscape, nude.f, nude.m):
data(arousal.df)
arousal.fit = lm(arousal ~ gender * picture, data = arousal.df)

## Create a data-frame with all pairwise comparisons using \code{emmeans}:
require(emmeans)
arousal.allpairs = pairs(emmeans(arousal.fit, ~gender * picture), infer = TRUE)

## Display only the within-level comparisons:
displayPairs(arousal.allpairs, levels1 = c('female', 'male'),
             levels2 = c('infant', 'landscape', 'nude.f', 'nude.m'))
```

Description

Plots the residuals versus the fitted (or predicted) values from a linear model. A horizontal line is drawn at $y = 0$, reflecting the fact that we expect the residuals to have a mean of zero. An optional lowess line is drawn if smoother is set to TRUE. This can be useful in determining whether a trend still exists in the residuals. An optional pair of lines is drawn at ± 2 times the standard deviation of the residuals - which is estimated from the Residual Mean Square (Within group mean square = WGMS). This can be useful in highlighting potential outliers. If the model has one or two factors and no continuous variables, i.e. if it is a oneway or twoway ANOVA model, and `levене = TRUE` then the P-value from Levene's test for equality variance is displayed in the top left hand corner, as long as the number of observations per group exceeds two.

Usage

```
eovcheck(x, ...)
```

```
## S3 method for class 'formula'
```

```
eovcheck(
  x,
  data = NULL,
  xlab = "Fitted values",
  ylab = "Residuals",
  col = NULL,
  smoother = FALSE,
  twosd = FALSE,
  levене = FALSE,
  ...
)
```

```
## S3 method for class 'lm'
```

```
eovcheck(x, smoother = FALSE, twosd = FALSE, levене = FALSE, ...)
```

Arguments

| | |
|-----------------------|---|
| <code>x</code> | A linear model formula. Alternatively, a fitted lm object from a linear model. |
| <code>...</code> | Optional arguments |
| <code>data</code> | A data frame in which to evaluate the formula. |
| <code>xlab</code> | a title for the x axis: see title . |
| <code>ylab</code> | a title for the y axis: see title . |
| <code>col</code> | a color for the lowess smoother line. |
| <code>smoother</code> | if TRUE then a smoothed lowess line will be added to the plot |
| <code>twosd</code> | if TRUE then horizontal dotted lines will be drawn at ± 2 sd |
| <code>levене</code> | if TRUE then the P-value from Levene's test for equality of variance is displayed |

Methods (by class)

- `eovcheck(formula)`: Testing for equality of variance plot
- `eovcheck(lm)`: Testing for equality of variance plot

See Also

[levene.test](#)

Examples

```
# one way ANOVA - oysters
data(oysters.df)
oyster.fit = lm(Oysters ~ Site, data = oysters.df)
eovcheck(oyster.fit)

# Same model as the previous example, but using eovcheck.formula
data(oysters.df)
eovcheck(Oysters ~ Site, data = oysters.df)

# A two-way model without interaction
data(soyabean.df)
soya.fit=lm(yield ~ planttime + cultivar, data = soyabean.df)
eovcheck(soya.fit)

# A two-way model with interaction
data(arousal.df)
arousal.fit = lm(arousal ~ gender * picture, data = arousal.df)
eovcheck(arousal.fit)

# A regression model
data(peru.df)
peru.fit = lm(BP ~ height + weight + age + years, data = peru.df)
eovcheck(peru.fit)

# A time series model
data(airpass.df)
t = 1:144
month = factor(rep(1:12, 12))
airpass.df = data.frame(passengers = airpass.df$passengers, t = t, month = month)
airpass.fit = lm(log(passengers)[-1] ~ t[-1] + month[-1]
                 + log(passengers)[-144], data = airpass.df)
eovcheck(airpass.fit)
```

Description

Calculates and prints Tukey multiple confidence intervals for contrasts in one or two-way ANOVA.

Usage

```
estimateContrasts(  
  contrast.matrix,  
  fit,  
  row = TRUE,  
  alpha = 0.05,  
  L = NULL,  
  FUN = identity  
)
```

Arguments

| | |
|------------------------------|---|
| <code>contrast.matrix</code> | a matrix of contrast coefficients. Separate rows of the matrix contain the contrast coefficients for that particular contrast, and a column for level of the factor. |
| <code>fit</code> | output from the <code>lm</code> function. |
| <code>row</code> | if TRUE, and the ANOVA is two-way, then contrasts in the row effects are printed, otherwise contrasts in the column effects are printed. Ignored if the ANOVA is one-way. |
| <code>alpha</code> | the nominal error rate for the multiple confidence intervals. |
| <code>L</code> | number of contrasts. If NULL, L will be set to the number of rows in the contrast matrix, otherwise L will be as specified. |
| <code>FUN</code> | optional function to be applied to estimates and confidence intervals. Typically for backtransformation operations. |

Value

Returns a matrix whose rows correspond to the different contrasts being estimated and whose columns correspond to the point estimate of the contrast, the Tukey lower and upper limits of the confidence interval, the unadjusted p-value, the Tukey and Bonferroni p-values.

Note

: This function is no longer exported as it should never be called by the user. It will ultimately be removed.

See Also

[summary1way](#), [summary2way](#), [multipleComp](#)

Examples

```
## computer data:
data(computer.df)
computer.df = within(computer.df, {selfassess = factor(selfassess)})
computer.fit = lm(score ~ selfassess, data = computer.df)
contrast.matrix = matrix(c(-1/2, -1/2, 1), byrow = TRUE, nrow = 1, ncol = 3)
contrast.matrix
s20x::estimateContrasts(contrast.matrix, computer.fit)
```

| | |
|---------|---|
| fire.df | <i>Fire Damage and Distance from the Fire Station</i> |
|---------|---|

Description

House damage and distance from the fire station, of 15 house fires. Data collected by an insurance company for homes in a particular area.

Format

A data frame with 15 observations on 2 variables.

| | | | |
|------|----------|---------|--|
| [,1] | damage | numeric | Damage (1000s of dollars) |
| [,2] | distance | numeric | Distance from the fire station (miles) |

| | |
|----------|---|
| freq1way | <i>Analysis of 1-dimensional frequency tables</i> |
|----------|---|

Description

If hypothprob is absent: prints confidence intervals for the true proportions, a Chi-square test for uniformity, confidence intervals for differences in proportions (no corrections for multiple comparisons and plots the proportions).

Usage

```
freq1way(
  counts,
  hypothprob,
  conf.level = 0.95,
  addCIs = TRUE,
  digits = 4,
  arrowwid = 0.1,
  estimated = 0
)
```

Arguments

| | |
|------------|---|
| counts | A 1-way frequency table as produced by <code>table</code> . |
| hypothprob | If present, a set of probabilities to test the cell counts against. |
| conf.level | confidence level for the confidence interval, expressed as a decimal. |
| addCIs | If true, adds confidence limits to plot of sample proportions. |
| digits | used to control rounding of printout. |
| arrowwid | controls width of arrowheads. |
| estimated | default is 0. Subtracted from the df for the Chi-square test. |

Details

If `hypothprob` is present: prints confidence intervals for the true proportions, a Chi-square test for the hypothesized probabilities, and plots the sample proportions (with attached confidence limits) alongside the corresponding hypothesized probabilities.)

Value

An invisible list containing the following components:

| | |
|-----|---|
| CIs | a matrix containing the confidence intervals. |
| exp | a vector of the expected counts. |
| chi | a vector of the components of Chi-square. |

Note

These confidence intervals have been Bonferroni adjusted for multiple comparisons. This function has been deprecated and will be removed from future versions of the package

Examples

```
##Body image data:
data(body.df)
eth.table = with(body.df, table(ethnicity))
freq1way(eth.table)
freq1way(eth.table, hypothprob=c(0.2,0.4,0.3,0.1))
```

fruitfly.df

*Fruitfly Data***Description**

This data gives fecundity for female fruitflies, *Drosophila melanogaster*. The fecundity is the number of eggs laid, per day, for the fruitfly's first 14 days of life. There are three strains: A control group, NS, Nonselected Strain, as well as RS, a strain bred for resistance to DDT and SS, a strain bred for susceptibility to DDT. Each strain contains 25 measurements. It is of interest to compare the level of fecundity across strains.

Format

A data frame with 75 observations on 2 variables.

| | | | |
|------|-----------|---------|--|
| [,1] | fecundity | numeric | Number of eggs laid, per day, per fruitfly |
| [,2] | strain | factor | Strain of fruitfly (NS, RS, SS) |

Source

A Handbook of Small Data Sets

References

Hand, D.J., Daly, F., Lunn, A.D., McConway, K.J. and Ostrowski, E. (1994). *A Handbook of Small Data Sets*. Boca Raton, Florida: Chapman and Hall/CRC.

Sokal, R.R. and Rohlf, F.J. (1981). *Biometry*, 2nd edition. San Francisco: W.H. Freeman, 239.

getVersion

*s20x package version number***Description**

Returns the version number of the s20x package. This is useful if a student is has problems running commands and the maintainer needs to check the version number.

Usage

```
getVersion()
```

Examples

```
getVersion()
```

| | |
|----------|---|
| house.df | <i>Sale and Advertised Prices of Houses</i> |
|----------|---|

Description

A random sample of 100 houses recently sold in Mt Eden, Auckland. For each house we have the advertised price and the actual sale price.

Format

A data frame with 100 observations on 2 variables.

| | | | |
|------|------------------|---------|----------------------------|
| [,1] | advertised.price | numeric | Advertised price (dollars) |
| [,2] | sell.price | numeric | Final sale price (dollars) |

| | |
|------------|----------------------------|
| incomes.df | <i>Mean Family Incomes</i> |
|------------|----------------------------|

Description

Random sample of 152 families giving their mean income (1000s of dollars). The sample was taken by an advertising agency over their area of operations.

| | |
|------------------|---|
| interactionPlots | <i>Interactions Plot for Two-way Analysis of Variance</i> |
|------------------|---|

Description

Displays data with intervals for each combination of the two factors and shows the mean differences between levels of the first factor for each level of the second factor. Note that there should be more than one observation for each combination of factors.

Usage

```
interactionPlots(y, ...)
```

```
## Default S3 method:
```

```
interactionPlots(
  y,
  fac1 = NULL,
  fac2 = NULL,
  xlab = NULL,
  xlab2 = NULL,
```

```

    ylab = NULL,
    data.order = TRUE,
    exlim = 0.1,
    jitter = 0.02,
    conf.level = 0.95,
    interval.type = c("tukey", "hsd", "lsd", "ci"),
    pooled = TRUE,
    tick.length = 0.1,
    interval.distance = 0.2,
    col.width = 2/3,
    xlab.distance = 0.1,
    xlen = 1.5,
    ylen = 1,
    ...
)

## S3 method for class 'formula'
interactionPlots(
  y,
  data = NULL,
  xlab = NULL,
  xlab2 = NULL,
  ylab = NULL,
  data.order = TRUE,
  exlim = 0.1,
  jitter = 0.02,
  conf.level = 0.95,
  interval.type = c("tukey", "hsd", "lsd", "ci"),
  pooled = TRUE,
  tick.length = 0.1,
  interval.distance = 0.2,
  col.width = 2/3,
  xlab.distance = 0.1,
  xlen = 1.5,
  ylen = 1,
  ...
)

```

Arguments

| | |
|------|---|
| y | either a formula of the form: $y \sim \text{fac1} + \text{fac2}$ where y is the response and fac1 and fac2 are the two explanatory variables used as factors, or a single response vector |
| ... | optional arguments. |
| fac1 | if 'y' is a vector, then fac1 contains the levels of factor 1 which correspond to the y value |
| fac2 | if 'y' is a vector, then fac1 contains the levels of factor 2 which correspond to the y value |

| | |
|--------------------------------|--|
| <code>xlab</code> | an optional label for the x-axis. If not specified the name of <code>fac1</code> will be used. |
| <code>xlab2</code> | an optional label for the lines. If not specified the name of <code>fac2</code> will be used. |
| <code>ylab</code> | An optional label for the y-axis. If not specified the name of <code>y</code> will be used. |
| <code>data.order</code> | if TRUE the levels of <code>fac1</code> and <code>fac2</code> will be set to <code>unique(fac1)</code> and <code>unique(fac2)</code> respectively. |
| <code>exlim</code> | provide extra limits. |
| <code>jitter</code> | the amount of horizontal jitter to show in the plot. The actual jitter is determined as the function is called, and will likely be different each time the function is used. |
| <code>conf.level</code> | confidence level of the intervals. |
| <code>interval.type</code> | four options for intervals appearing on plot: <code>'tukey'</code> , <code>'hsd'</code> , <code>'lsd'</code> or <code>'ci'</code> . |
| <code>pooled</code> | two options: pooled or unpooled standard deviation used for plotted intervals. |
| <code>tick.length</code> | size of tick, in inches. |
| <code>interval.distance</code> | distance, as a fraction of the column width, between the points and interval. This is in addition to the extra space allocated for the jitter. |
| <code>col.width</code> | width of a factor 'column', as a fraction of the space between the centres of two columns. |
| <code>xlab.distance</code> | distance of x-axis labels from bottom of plot, as a fraction of the overall height of the plot. |
| <code>xlen, ylen</code> | character interspacing factor for horizontal (x) and vertical (y) spacing of the legend. |
| <code>data</code> | an optional data frame containing the variables in the model. |

Methods (by class)

- `interactionPlots(default)`: Interactions Plot for Two-way Analysis of Variance
- `interactionPlots(formula)`: Interactions Plot for Two-way Analysis of Variance

See Also

[summary2way.](#)

Examples

```
data(mtcars)
interactionPlots(wt ~ vs + gear, mtcars)

## note this usage is deprecated
data(mtcars)
with(mtcars, interactionPlots(wt, vs, gear))
```

| | |
|-------------|--|
| lakemary.df | <i>Ages and Lengths of Lake Mary Bluegills</i> |
|-------------|--|

Description

The ages and lengths of 78 bluegills captured from Lake Mary, Minnesota.

Format

A data frame with 78 observations on 2 variables.

| | | | |
|------|--------|---------|-------------------------|
| [,1] | Age | numeric | Age of the fish (years) |
| [,2] | Length | numeric | Length at capture (mm) |

| | |
|-----------|-----------------------------|
| larain.df | <i>Los Angeles Rainfall</i> |
|-----------|-----------------------------|

Description

Annual rainfall (in inches) for Los Angeles from 1908 to 1973.

Format

A time series with 66 observations.

| | |
|-----------|---------------|
| layout20x | <i>Layout</i> |
|-----------|---------------|

Description

Allows an numRows by numCols matrix of plots to be displayed in a single plot. If the function is called with no arguments, then the plotting device layout will be reset to a single plot.

Usage

```
layout20x(numRows = 1, numCols = 1)
```

Arguments

| | |
|---------|---------------------------------|
| numRows | number of rows in plot array |
| numCols | number of columns in plot array |

Value

Function returns no value

Note

This function is deprecated. It will be removed in future versions of the package.

Examples

```
data(course.df)
layout20x(1,2)
stripchart(course.df$Exam)
boxplot(course.df$Exam)
```

levene.test

Levene test for the ANOVA Assumption

Description

Perform a Levene test for equal group variances in both one-way and two-way ANOVA. A table with the results is (normally) displayed.

Usage

```
levene.test(formula, data, digit = 5, show.table = TRUE)
```

Arguments

| | |
|------------|---|
| formula | a symbolic description of the model to be fitted: response ~ fac1 + fac2. |
| data | an optional data frame containing the variables in the model. |
| digit | the number of decimal places to display. |
| show.table | If this argument is FALSE then the output will be suppressed |

Value

A list with the following elements:

| | |
|---------|---------------------|
| df | degrees of freedom. |
| ss | sum squares. |
| ms | mean squares. |
| f.value | F-statistic value. |
| p.value | P-value. |

See Also

[crossFactors](#), [anova](#).

Examples

```
##
data(computer.df)
levene.test(score ~ factor(selfassess), computer.df)
```

| | |
|----------|-------------------------------------|
| mazda.df | <i>Year and Price of Mazda Cars</i> |
|----------|-------------------------------------|

Description

Prices and ages of 124 Mazda cars collected from the Melbourne Age newspaper in 1991.

Format

A data frame with 124 observations on 2 variables.

| | | | |
|------|-------|---------|----------------------------|
| [,1] | price | numeric | Price (Australian dollars) |
| [,2] | year | numeric | Year of manufacture |

| | |
|-----------|---|
| mening.df | <i>Monthly Notifications of Meningococcal Disease</i> |
|-----------|---|

Description

This data shows the monthly number of notifications meningococcal disease in New Zealand from January 1990 to December 2001.

Format

A data frame with 144 observations on 3 variables: Month, Year and mening.

| | |
|------------|--------------------|
| mergers.df | <i>Merger Days</i> |
|------------|--------------------|

Description

A random selection of 38 consummated mergers from the USA, 1982, giving the number of days between the date the merger was announced and the date the merger became effective.

Description

Plots four model checking plots: an pred-res plot (residuals against predicted values), a Normal Quantile-Quantile (Q-Q) plot, a histogram of the residuals with a normal distribution super-imposed and a Cook's Distance plot.

Usage

```
modcheck(x, ...)

## S3 method for class 'lm'
modcheck(
  x,
  plotOrder = 1:4,
  args = list(eovcheck = list(smoother = FALSE, twosd = FALSE, levene = FALSE, ...),
             normcheck = list(xlab = c("Theoretical Quantiles", ""), ylab = c("Sample Quantiles",
             "")), main = c("", ""), col = "light blue", bootstrap = FALSE, B = 5, bpch = 3, bcol =
             "lightgrey", shapiro.wilk = FALSE, whichPlot = 1:2, usePar = TRUE, ...), cooks20x =
             list(main = "Cook's Distance plot", xlab = "observation number", ylab =
             "Cook's distance", line = c(0.5, 0.1, 2), cex.labels = 1, axisOpts = list(xAxis =
             TRUE), ...)),
  parVals = list(mfrow = c(2, 2), xaxs = "r", yaxs = "r", pty = "s", mai = c(0.2, 0.2,
             0.05, 0.05)),
  ...
)
```

Arguments

| | |
|-----------|---|
| x | a vector of observations, or the residuals from fitting a linear model. Alternatively, a fitted <code>lm</code> object. If <code>x</code> is a single vector, then the implicit assumption is that the mean (or null) model is being fitted, i.e. <code>lm(x ~ 1)</code> and that the data are best summarised by the sample mean. |
| plotOrder | the order of the plots. 1: pred-res plot, 2: normal Q-Q plot, 3: histogram, 4: Cook's Distance plot. |
| args | a list containing three additional lists <code>eovcheckArgs</code> , <code>normcheckArgs</code> and <code>cooksArgs</code> . The elements of these lists are the optional arguments of <code>eovcheck</code> , <code>normcheck</code> and <code>cooks20x</code> , and are explained in more detail in those functions. Most users will never use these arguments, but they provide super-flexibility in terms of what is displayed. |
| parVals | the values that are set via <code>par</code> for this plot. These are <code>mfrow</code> , <code>xaxs</code> , <code>yaxs</code> , <code>pty</code> , and <code>mai</code> . Most users will never use these arguments, but they provide super-flexibility in terms of what is displayed. |
| ... | additional paramaters. Included for future flexibility, but unsure how this might be used currently. |

Methods (by class)

- `modcheck(lm)`: Model checking plots

Examples

```
# An exponential growth curve
e = rnorm(100, 0, 0.1)
x = rnorm(100)
y = exp(5 + 3 * x + e)
fit = lm(y ~ x, data = data.frame(x, y))
modcheck(fit)

# An exponential growth curve with the correct transformation
fit = lm(log(y) ~ x, data = data.frame(x, y))
modcheck(fit)

# Peruvian Indians data
data(peru.df)
modcheck(lm(BP ~ weight, data = peru.df))
```

modelcheck

Model checking plots Compact layout for model checking plots.

Description

Model checking plots Compact layout for model checking plots.

Usage

```
modelcheck(x, ...)

## S3 method for class 'lm'
modelcheck(x, which = 1:3, mar = c(3, 4, 1.5, 4), ...)
```

Arguments

| | |
|--------------------|---|
| <code>x</code> | The fitted model. |
| <code>which</code> | The plot(s) to be drawn. Residuals vs fitted values (<code>which = 1</code>), histogram and QQ plot of residuals (<code>which = 2</code>), Cook's distance plot (<code>which = 3</code>). |
| <code>mar</code> | Margins applied to each selected plot. |
| <code>...</code> | any other arguments to pass to <code>plot</code> |

Methods (by class)

- `modelcheck(lm)`: Model checking plots

Examples

```
x = 1:30
y = rnorm(30)
lm.fit = lm(y~x)
# Plot resids vs fitted only
modelcheck(lm.fit, 1)

# Plot resids vs fitted, and histogram and QQ plot
modelcheck(lm.fit, 1:2)

# Plot all
modelcheck(lm.fit)
```

| | |
|-----------|-------------------------------------|
| mozart.df | <i>Length of Mozart's Movements</i> |
|-----------|-------------------------------------|

Description

Length of movements from 11 of Mozart's early symphonies and 11 of his late symphonies.

Format

A data frame with 88 observations on 3 variables.

| | | | |
|------|----------|---------|--|
| [,1] | Time | numeric | Time of each movement (seconds) |
| [,2] | Movement | factor | Movement (M1, M2, M3, M4) |
| [,3] | Period | factor | Period that the symphony was written (early, late) |

| | |
|--------------|-----------------------------|
| multipleComp | <i>Multiple Comparisons</i> |
|--------------|-----------------------------|

Description

Calculates and prints the estimate, multiple 95% confidence intervals; unadjusted, Tukey and Bonferroni p-values for all possible differences in means in a one-way ANOVA.

Usage

```
multipleComp(fit, conf.level = 0.95, FUN = identity)
```

Arguments

| | |
|------------|---|
| fit | output from the command 'lm()'. |
| conf.level | confidence level for the confidence interval, expressed as a percentage. |
| FUN | optional function to be applied to estimates and confidence intervals. Typically for backtransformation operations. |

Value

Returns a list of estimates, confidence intervals and p-values.

Examples

```
## computer data
data(computer.df)
fit = lm(score ~ factor(selfassess), data = computer.df)
multipleComp(fit)

## butterfat data
data("butterfat.df")
fit <- lm(log(Butterfat) ~ Breed, data=butterfat.df)
multipleComp(fit, FUN=exp)
```

| | |
|---------|-------------------------|
| nail.df | <i>Nail Polish Data</i> |
|---------|-------------------------|

Description

These data were collected to determine whether quick drying nail polish or regular nail polish dried faster. The time for each type of nail polish to dry was recorded.

Format

A data frame with 60 observations on 2 variables.

| | | | |
|------|--------|---------|---|
| [,1] | polish | factor | Type of polish (Regular, Quick) |
| [,2] | dry | integer | Time (in seconds) for the polish to dry |

| | |
|-----------|-----------------------------------|
| normcheck | <i>Testing for normality plot</i> |
|-----------|-----------------------------------|

Description

Plots two plots side by side. Firstly it draws a Normal QQ-plot of the residuals, along with a line which has an intercept at the mean of the residuals and a slope equal to the standard deviation of the residuals. If `shapiro.wilk = TRUE` then, in the top left hand corner of the Q-Q plot, the P-value from the Shapiro-Wilk test for normality is given. Secondly, it draws a histogram of the residuals. A normal distribution is fitted and superimposed over the histogram. NOTE: if you want to leave the x-axis blank in the histogram then, use `xlab = c("Theoretical Quantiles", " ")`, i.e. leave a space between the quotes. If you don't leave a space, then information will be extracted from x.

Usage

```

normcheck(x, ...)

## Default S3 method:
normcheck(
  x,
  xlab = c("Theoretical Quantiles", ""),
  ylab = c("Sample Quantiles", ""),
  main = c("", ""),
  col = "light blue",
  bootstrap = FALSE,
  B = 5,
  bpch = 3,
  bcol = "lightgrey",
  shapiro.wilk = FALSE,
  whichPlot = 1:2,
  usePar = TRUE,
  ...
)

## S3 method for class 'lm'
normcheck(
  x,
  xlab = c("Theoretical Quantiles", ""),
  ylab = c("Sample Quantiles", ""),
  main = c("", ""),
  col = "light blue",
  bootstrap = FALSE,
  B = 5,
  bpch = 3,
  bcol = "lightgrey",
  shapiro.wilk = FALSE,
  whichPlot = 1:2,
  usePar = TRUE,
  ...
)

```

Arguments

| | |
|-------------------|--|
| <code>x</code> | the residuals from fitting a linear model. Alternatively, a fitted <code>lm</code> object. |
| <code>...</code> | additional arguments which are passed to both <code>qqnorm</code> and <code>hist</code> |
| <code>xlab</code> | a title for the x-axis of both the Q-Q plot and the histogram: see title . |
| <code>ylab</code> | a title for the y-axis of both the Q-Q plot and the histogram: see title . |
| <code>main</code> | a title for both the Q-Q plot and the histogram: see title . |
| <code>col</code> | a color for the bars of the histogram. |

| | |
|--------------|---|
| bootstrap | if TRUE then B samples will be taken from a Normal distribution with the same mean and standard deviation as x. These will be plotted in a lighter colour behind the empirical quantiles so that we can see how much variation we would expect in the Q-Q plot for a sample of the same size from a truly normal distribution. |
| B | the number of bootstrap samples to take. Five should be sufficient, but hey maybe you want more? |
| bpch | the plotting symbol used for the bootstrap samples. Legal values are the same as any legal value for pch as defined in par . |
| bcol | the plotting colour used for the bootstrap samples. Legal values are the same as any legal value for col as defined in par . |
| shapiro.wilk | if TRUE, then in the top left hand corner of the Q-Q plot, the P-value from the Shapiro-Wilk test for normality is displayed. |
| whichPlot | legal values are 1, 2, and any pair of the two, i.e. 1:2, 2:1, c(1,2), c(2,1), or even variants of c(1,1) (although I do not know why you would) want to do this. 1:2 is used by default and returns a normal Q-Q plot and a histogram of the residuals in that order. The order of the labels in xlab and ylab assume this order, and will be reordered automatically if the order is anything other than 1:2. |
| usePar | if TRUE, then this function will set par for the user. If FALSE, then this function assumes par has been set by the user and therefore should not be over-ridden. |

Methods (by class)

- normcheck(default): Testing for normality plot
- normcheck(lm): Testing for normality plot

See Also

[shapiro.test](#).

Examples

```
# An exponential growth curve
e = rnorm(100, 0, 0.1)
x = rnorm(100)
y = exp(5 + 3 * x + e)
fit = lm(y ~ x)
normcheck(fit)

# An exponential growth curve with the correct transformation
fit = lm(log(y) ~ x)
normcheck(fit)

# Same example as above except we use normcheck.default
normcheck(residuals(fit))

# Peruvian Indians data
```

```
data(peru.df)
normcheck(lm(BP ~ weight, data = peru.df))
```

onewayPlot

One-way Analysis of Variance Plot

Description

Displays stripplot/boxplot of the response variable with intervals by factor levels. It is used as part of a one-way ANOVA analysis.

Usage

```
onewayPlot(x, ...)

## Default S3 method:
onewayPlot(
  x,
  f,
  conf.level = 0.95,
  interval.type = "tukey",
  pooled = TRUE,
  strip = TRUE,
  vert = TRUE,
  verbose = FALSE,
  ylabel = deparse(terms(formula)[[2]]),
  flabel = deparse(terms(formula)[[3]]),
  ...
)

## S3 method for class 'formula'
onewayPlot(
  formula,
  data = parent.frame(),
  conf.level = 0.95,
  interval.type = "tukey",
  pooled = TRUE,
  strip = TRUE,
  vert = TRUE,
  verbose = FALSE,
  ylabel = deparse(terms(formula)[[2]]),
  flabel = deparse(terms(formula)[[3]]),
  ...
)

## S3 method for class 'lm'
onewayPlot(x, ..., ylabel = nms[1], flabel = nms[2])
```

Arguments

| | |
|---------------|---|
| x | a vector of responses, a formula object or an lm object |
| ... | optional arguments. |
| f | if x is a vector of responses then f contains the group labels for each observation in x. That is, the ith value in f says which group the ith observation of x belongs to. |
| conf.level | confidence level of the intervals. |
| interval.type | three options for intervals appearing on plot: 'hsd', 'lsd' or 'ci'. |
| pooled | two options: pooled or unpooled standard deviation used for plotted intervals. |
| strip | if strip=F, boxplots are displayed instead. |
| vert | if vert=F, horizontal stripplots are displayed instead (boxplots can only be displayed vertically). |
| verbose | if true, print intervals on console. |
| ylabel | can be used to replace variable name of y by another string. |
| flabel | can be used to replace variable name of f by another string. |
| formula | a symbolic description of the model to be fit. |
| data | an optional data frame in which to evaluate the formula. |

Methods (by class)

- onewayPlot(default): One-way Analysis of Variance Plot
- onewayPlot(formula): One-way Analysis of Variance Plot
- onewayPlot(lm): One-way Analysis of Variance Plot

See Also

[summary1way](#), [t.test](#).

Examples

```
##see example in 'summary1way'

##computer data:
data(computer.df)
onewayPlot(score~selfassess, data = computer.df)

##apple data:
data(apples.df)
twosampPlot(Weight~Propagated, data = apples.df)

##oyster data:
data(oysters.df)
onewayPlot(log(Oysters)~Site, data = oysters.df)

##oyster data:
```

```
data(oysters.df)
oyster.fit = lm(log(Oysters)~Site, data = oysters.df)
onewayPlot(oyster.fit)
```

| | |
|------------|---|
| oysters.df | <i>Oyster Abundances over Different Sites</i> |
|------------|---|

Description

Data from an experiment to determine the abundance of oysters recruiting from three sites in two different estuaries in New South Wales. One in Georges River and two in Port Stephens. The number of oysters were recorded for 10 cm by 10 cm panels over a two year period.

Format

A data frame with 87 observations on 2 variables.

| | | | |
|------|---------|---------|--|
| [,1] | Oysters | numeric | Number of oysters on each experimental panel |
| [,2] | Site | factor | Location of the experimental panels (GR = Georges River, PS1 = First Port Stephens Site, PS2 = S |

| | |
|----------|--|
| pairs20x | <i>Pairwise Scatter Plots with Histograms and Correlations</i> |
|----------|--|

Description

Plots pairwise scatter plots with histograms and correlations for the data frame.

Usage

```
pairs20x(x, na.rm = TRUE, ...)
```

Arguments

| | |
|-------|--|
| x | a data frame. |
| na.rm | if TRUE then only complete cases will be displayed |
| ... | optional arguments which are passed to the generic pairs function. |

Value

Returns the plots.

See Also

'pairs', 'panel.smooth', 'panel.cor', 'panel.hist'

Examples

```
##peruvian indians
data(peru.df)
pairs20x(peru.df)
```

| | |
|---------|-------------------------|
| peru.df | <i>Peruvian Indians</i> |
|---------|-------------------------|

Description

A random sample of Peruvian Indians born in the Andes mountains, but who have since migrated to lower altitudes. The sample was collected to assess the long term effects of altitude on blood pressure.

Format

A data frame with 39 observations on 5 variables.

| | | | |
|------|--------|---------|---|
| [,1] | age | numeric | Subject's age |
| [,2] | years | numeric | Number of years since migration |
| [,3] | weight | numeric | Subject's weight (kg) |
| [,4] | height | numeric | Subject's height (mm) |
| [,5] | BP | numeric | Subject's systolic blood pressure (mm Hg) |

| | |
|------------|---|
| predict20x | <i>Model Predictions for a Linear Model</i> |
|------------|---|

Description

Uses the main output and some error messages from R function 'predict' but gives you more output. (Error messages are not reliable when used in Splus.)

Usage

```
predict20x(object, newdata, cilevel = 0.95, digit = 3, print.out = TRUE, ...)
```

Arguments

| | |
|-----------|---|
| object | an lm object, i.e. the output from lm. |
| newdata | prediction data frame. |
| cilevel | confidence level of the interval. |
| digit | decimal numbers after the point. |
| print.out | if TRUE, print out the prediction matrix. |
| ... | optional arguments that are passed to the generic 'predict' |

Details

Note: The data frame, `newdata`, must have the same column order and data types (e.g. numeric or factor) as those used in fitting the model.

Value

| | |
|-----------------------------|--|
| <code>frame</code> | vector or matrix including predicted values, confidence intervals and predicted intervals. |
| <code>fit</code> | prediction values. |
| <code>se.fit</code> | standard error of predictions. |
| <code>residual.scale</code> | residual standard deviations. |
| <code>df</code> | degrees of freedom for residual. |
| <code>cilevel</code> | confidence level of the interval. |

Note

This function is deprecated. It will be removed in future versions of the package.

this function is deprecated as it is never used in class any more. We prefer the standard [predict](#) method.

See Also

[predict](#), [predict.lm](#), [as.data.frame](#).

Examples

```
# Zoo data
data(zoo.df)
zoo.df = within(zoo.df, {day.type = factor(day.type)})
zoo.fit = lm(log(attendance) ~ time + sun.yesterday + nice.day + day.type + tv.ads,
             data = zoo.df)
pred.zoo = data.frame(time = 8, sun.yesterday = 10.8, nice.day = 0,
                     day.type = factor(3), tv.ads = 1.181)
predict20x(zoo.fit, pred.zoo)

# Peruvian Indians data
data(peru.df)
peru.fit = lm(BP ~ age + years + I(years^2) + weight + height, data = peru.df)
pred.peru = data.frame(age = 21, years = 2, `I(years^2)` = 2, weight = 71, height = 1629)
predict20x(peru.fit, pred.peru)
```

| | |
|--------------|--|
| predictCount | <i>Predicted Counts for a Generalized Linear Model</i> |
|--------------|--|

Description

Uses the main output and some error messages from R function 'predict' but gives you more output. (Error messages are not reliable when used in Splus.)

Usage

```
predictCount(object, newdata, cilevel = 0.95, digit = 3, print.out = TRUE, ...)
```

Arguments

| | |
|-----------|--|
| object | a glm object, i.e. the output from glm . |
| newdata | prediction data frame. |
| cilevel | confidence level of the interval. |
| digit | decimal numbers after the point. |
| print.out | if TRUE, print out the prediction matrix. |
| ... | optional arguments that are passed to the generic predict. |

Details

Note: The data frame, newdata, must have the same column order and data types (e.g. numeric or factor) as those used in fitting the model.

Value

A data frame with three columns:

Predicted the predicted count.

Conf.lower the lower bound of the predicted count.

Conf.upper the upper bound of the predicted count.

See Also

[predict](#), [predict.glm](#), [as.data.frame](#).

Description

An alternative to [predictCount](#) to handle Binomial as well as Poisson models

Usage

```
predictGLM(object, newdata, type = "link", cilevel = 0.95, quasit = FALSE, ...)
```

Arguments

| | |
|---------|--|
| object | a glm object, i.e. the output from glm . |
| newdata | prediction data frame. |
| type | "link" (default) or "response" for CI on linear predictor or response scale. |
| cilevel | confidence level of the interval. |
| quasit | if TRUE, t multiplier for CI rather than normal multiplier in the case of a quasi model. |
| ... | optional arguments that are passed to the generic <code>predict</code> . |

Details

Note: The data frame, `newdata`, must have the same column order and data types (e.g. numeric or factor) as those used in fitting the model.

Value

A data frame with three columns:

Predicted the predicted count.

Conf.lower the lower bound of the predicted count.

Conf.upper the upper bound of the predicted count.

See Also

[predict](#), [predict.glm](#), [as.data.frame](#).

prop`lsd.new` *LSD-Display Intervals*

Description

This function is called by `rowdistr`.

Usage

```
proplsd.new(crosstablist, conf.level = 0.95, arrowlength = 0.1)
```

Arguments

| | |
|---------------------------|---|
| <code>crosstablist</code> | A list produced by <code>crosstabs</code> or a matrix containing a 2-way table of counts (without marginal totals). |
| <code>conf.level</code> | Confidence level of the intervals. |
| <code>arrowlength</code> | Length of the arrows. |

Note

This function is no longer exported as it should never be called by the user. It is also deprecated and will be removed from future versions of the package.

See Also

`crosstabs`, `rowdistr`

rain.df *Cloud Seeding and Levels of Rainfall*

Description

Data from an experiment to see if seeding clouds with Silver Nitrate effects the amount of rainfall.

Format

A data frame with 50 observations on 2 variables.

| | | | |
|------|------|---------|---|
| [,1] | rain | numeric | Amount of rain |
| [,2] | seed | factor | Whether the clouds are seeded or not (seeded, unseeded) |

Source

Chambers, Cleveland, Kleiner, Tukey. (1983). Graphical Methods for Data Analysis.

`residPlot`*Fitted values versus residuals plot*

Description

Plots a scatter plot for the variables of the residuals and fitted values from the linear model, `lmfit`. A lowess smooth line for the underlying trend, as well as one standard deviation error bounds for the scatter about this trend, are added to this scatter plot. A test for a quadratic relationship between the residuals and the fitted values is also computed.

Usage

```
residPlot(lmfit, f = 0.5)
```

Arguments

| | |
|--------------------|--|
| <code>lmfit</code> | an <code>lm</code> object, i.e. the output from <code>lm</code> . |
| <code>f</code> | the smoother span. This gives the proportion of points in the plot which influence the smooth at each value. Larger values give more smoothness. |

Value

Returns the plot.

Note

This function is deprecated. It will be removed in future versions of the package.

See Also

[trendscatter](#)

Examples

```
# Peruvian Indians data
data(peru.df)
fit=lm(BP~age+years+weight+height, data = peru.df)
residPlot(fit)
```

| | |
|----------|---|
| rowdistr | <i>Row distributions from a cross-tabulation of two variables</i> |
|----------|---|

Description

Produces summaries and plots from a cross-tabulation. The output produced depends on the parameter 'comp'. Columns relate to response categories and rows to different populations.

Usage

```
rowdistr(  
  crosstablist,  
  comp = c("basic", "within", "between"),  
  conf.level = 0.95,  
  plot = TRUE,  
  suppressText = FALSE  
)
```

Arguments

| | |
|--------------|--|
| crosstablist | a list produced by 'crosstabs' or a matrix containing a 2-way table of counts (without marginal totals). |
| comp | three options: 'basic' (default), 'within', and 'between'. |
| conf.level | confidence level of the intervals. |
| plot | if FALSE then the row distribution plots are not displayed |
| suppressText | if TRUE then text results are not displayed |

Details

The 'basic' option (default) produces the response distribution for each row population together with comparative bar charts.

If comp = 'between' the resulting output displays how the probability of falling into a response class (column) differs between populations. Confidence intervals for differences in proportions are produced together with a set of barcharts with LSD intervals.

If comp = 'within' the resulting output shows the extent to which the component probabilities of the same row distribution differ. Separate Chi-square tests for uniformity are produced for each row distribution as are confidence intervals for differences in proportions within the same distribution.

Arguments plot and suppressText are really only used when producing knitr or Sweave documents so that just the plot or just the text can be displayed in the document.

Value

A matrix of row proportions, i.e cell counts divided by row marginals.

See Also[crosstabs](#)**Examples**

```

data(body.df)
z = crosstabs(~ ethnicity + married, data = body.df)
rowdistr(z)
rowdistr(z, comp='between')
rowdistr(z, comp='within')

##from matrix of counts
z = matrix(c(4,3,2,6,47,20,40,62,11,8,7,22,3,0,1,10), 4, 4)
rowdistr(z)

```

| | |
|----|------------------|
| rr | <i>Read Data</i> |
|----|------------------|

Description

For internal use

Usage

```
rr()
```

| | |
|----------|-------------------|
| seeds.df | <i>Seeds Data</i> |
|----------|-------------------|

Description

These data record the number of seeds (out of 100) that germinated when given different amounts of water. The seeds were either exposed to light or kept in the dark. Four identical boxes were used for each combination of water and light

Format

A data frame with 48 observations on 3 variables.

| | | | |
|------|-------|---------|--|
| [,1] | Light | integer | Seeds exposed to light (N=No, Y=Yes) |
| [,2] | Water | integer | Amount of water, higher levels correspond to more water (1, 2, 3, 4, 5, 6) |
| [,3] | Count | integer | Number of seeds that germinated (out of 100) |

| | |
|----------|-------------------|
| sheep.df | <i>Sheep Data</i> |
|----------|-------------------|

Description

Sheep Data

Format

A data frame with 100 observations on 3 variables.

| | | | |
|------|--------|---------|------------------|
| [,1] | Weight | integer | . |
| [,2] | Copper | factor | levels (No, Yes) |
| [,3] | Cobalt | factor | levels (No, Yes) |

| | |
|----------|---------------------------|
| skewness | <i>Skewness Statistic</i> |
|----------|---------------------------|

Description

Calculates the skewness statistic of the data in 'x'. Values close to zero correspond to reasonably symmetric data, positive values of this measure indicate right-skewed data whereas negative values indicate left-skewness.

Usage

```
skewness(x, ...)
```

Arguments

| | |
|-----|---|
| x | vector containing the data. |
| ... | any other variables to be passed to mean and sd, e.g. na.rm = TRUE. |

Value

Returns the value of the skewness.

Examples

```
##Merger data:
data(mergers.df)
skewness(mergers.df$mergerdays)
```

 skulls.df

Skulls Data

Description

Male Egyptian skulls from five different epochs. Each skull has had four measurements taken of it, BH, Basibregmatic Height, BL, Basialveolar Length, MB, Maximum Breadth and NH, Nasal Height. It is of interest to investigate the change in shape over time. A gradual change, would indicate inbreeding of the populations. This data only includes the maximum breadth measurements.

Format

A data frame with 150 observations on 2 variables.

| | | |
|------|-------------|---------|
| [,1] | measurement | integer |
| [,2] | year | integer |

Source

A Handbook of Small Data Sets

References

Hand, D.J., Daly, F., Lunn, A.D., McConway, K.J. and Ostrowski, E. (1994). *A Handbook of Small Data Sets*. Boca Raton, Florida: Chapman and Hall/CRC.

Thomson, A. and Randall-Maciver, R. (1905). *Ancient Races of the Thebaid*. Oxford: Oxford University Press.

 snapper.df

Snapper Weight Data

Description

Weight and length measurements of 844 snapper (*Pagrus auratus*) caught in the Hauraki Gulf, near Auckland, New Zealand.

Format

A data frame with 844 observations on 2 variables.

len Fork length in centimetres. The fork length of a fish measured from the tip of the snout to the end of the middle caudal fin rays and is used in fishes in which it is difficult to tell where the vertebral column ends. Essentially it is the measurement from the tip of the 'nose' of the fish to the 'vee' in the tail.

wgt Weight of the fish in kilograms (kg).

Source

Russell Millar, University of Auckland.

 soyabean.df

Soya Bean Yields

Description

Data from an experiment to examine the effects of different planting times on the yield of soya beans, given four different cultivars.

Format

A data frame with 32 observations on 3 variables.

| | | | |
|------|-----------|---------|--|
| [,1] | yield | numeric | Yield of each plant |
| [,2] | cultivar | factor | Cultivar used (cult1, cult2, cult3, cult4) |
| [,3] | planttime | factor | Month of planting (Novemb, Decemb) |

Source

Littler, R. University of Waikato

 stripqq

Strip charts and normal quantile-quantile plots

Description

Draws strip charts and normal quantile quantile plots of x for each value of the grouping variable g

Usage

```
stripqq(formula, ...)

## S3 method for class 'formula'
stripqq(formula, data = NULL, ...)
```

Arguments

| | |
|---------|---|
| formula | A symbolic specification of the form $x \sim g$ can be given, indicating the observations in the vector 'x' are to be grouped according to the levels of the factor 'g'. NAs are allowed in the data. |
| data | An optional data frame in which to evaluate the formula |
| ... | Optional arguments that are passed to the stripchart function. |

Methods (by class)

- stripqq(formula): Strip charts and normal quantile-quantile plots

Note

This function is deprecated and will be removed in later versions of the package.

Examples

```
## Zoo data
data(zoo.df)
stripqq(attendance~day.type, data = zoo.df)
```

summary1way

One-way Analysis of Variance Summary

Description

Displays summary information for a one-way anova analysis. The `lm` object must come from a numerical response variable and a single factor. The output includes: (i) anova table; (ii) numeric summary; (iii) table of effects; (iv) plot of data with intervals.

Usage

```
summary1way(
  fit,
  digit = 5,
  conf.level = 0.95,
  inttype = "tukey",
  pooled = TRUE,
  print.out = TRUE,
  draw.plot = TRUE,
  ...
)
```

Arguments

| | |
|-------------------------|--|
| <code>fit</code> | an <code>lm</code> object, i.e. the output from <code>lm</code> . |
| <code>digit</code> | decimal numbers after the point. |
| <code>conf.level</code> | confidence level of the intervals. |
| <code>inttype</code> | three options for intervals appeared on plot: <code>'hsd'</code> , <code>'lsd'</code> or <code>'ci'</code> . |
| <code>pooled</code> | two options: pooled or unpooled standard deviation used for plotted intervals. |
| <code>print.out</code> | if TRUE, print out the output on the screen. |
| <code>draw.plot</code> | if TRUE, plot data with intervals. |
| <code>...</code> | more options. |

Value

| | |
|---------------|--|
| Df | degrees of freedom for regression, residual and total. |
| Sum of Sq | sum squares for regression, residual and total. |
| Mean Sq | mean squares for regression and residual. |
| F value | F-statistic value. |
| Pr(F) | |
| Main Effect | |
| Group Effects | |

See Also

[summary2way](#), [anova](#), [aov](#), [dummy.coef](#), [onewayPlot](#)

Examples

```
attitudes = c(5.2,5.2,6.1,6,5.75,5.6,6.25,6.8,6.87,7.1,
             6.3,6.35,5.5,5.75,4.6,5.36,5.85,5.9)
l = rep(c('Gp1','Gp2','Gp3'),rep(6,3))
l = factor(l)
f = lm(attitudes ~ l)
result = summary1way(f)
result
```

summary2way

Two-way Analysis of Variance Summary

Description

Displays summary information for a two-way anova analysis. The lm object must come from a numerical response variable and factors. The output depends on the value of page:

Usage

```
summary2way(
  fit,
  page = c("table", "means", "effects", "interaction", "nointeraction"),
  digit = 5,
  conf.level = 0.95,
  print.out = TRUE,
  new = TRUE,
  all = FALSE,
  FUN = "identity",
  ...
)
```

Arguments

| | |
|-------------------------|--|
| <code>fit</code> | an lm object, i.e. the output from <code>'lm()'</code> . |
| <code>page</code> | options for output: <code>'table'</code> , <code>'means'</code> , <code>'effects'</code> , <code>'interaction'</code> , <code>'nointeraction'</code> |
| <code>digit</code> | the number of decimal places in the display. |
| <code>conf.level</code> | confidence level of the intervals. |
| <code>print.out</code> | if TRUE, print out the output on the screen. |
| <code>new</code> | if TRUE then this will run the new version of <code>summary2way</code> which should be more robust than the old version. It does not work in the same way however. In particular, when <code>page = 'means'</code> it does not return summary statistics for each grouping of the data (pooled/by row factor/by column factor/by interaction factor). Instead it simply returns the means for each grouping. |
| <code>all</code> | Only applicable to <code>page = "interaction"</code> . If TRUE, pairwise comparisons for all combinations of factor levels are shown. Otherwise, comparisons are only shown between combinations that have the same level for one of the factors. |
| <code>FUN</code> | optional function to be applied to estimates and confidence intervals. Typically for backtransformation operations. |
| <code>...</code> | other arguments like <code>inttype</code> , <code>pooled</code> etc. |

Details

`page = 'table'` anova table `page = 'means'` cell means matrix, numeric summary `page = 'effects'` table of effects `page = 'interaction'` tables of contrasts `page = 'nointeraction'` tables of contrasts

Value

A list with the following components:

| | |
|----------------------------------|--|
| <code>Df</code> | degrees of freedom for regression, residual and total. |
| <code>Sum of Sq</code> | sum squares for regression, residual and total. |
| <code>Mean Sq</code> | mean squares for regression and residual. |
| <code>F value</code> | F-statistic value. |
| <code>Pr(F)</code> | The P-value associated with each F-test. |
| <code>Grand Mean</code> | The overall mean of the response variable. |
| <code>Row Effects</code> | The main effects for the first (row) factor. |
| <code>Col Effects</code> | The main effects for the second (column) factor. |
| <code>Interaction Effects</code> | The interaction effects if an interaction model has been fitted, otherwise NULL. |
| <code>results</code> | If <code>new = TRUE</code> , then this is a list with five components: <code>table</code> - the ANOVA table, <code>means</code> the table of means from <code>model.tables</code> , <code>effects</code> - the table of effects from <code>model.tables</code> , and <code>comparisons</code> - the differences in the means with standard errors, confidence bounds, and P-values from TukeyHSD |

See Also

[summary1way](#), [model.tables](#), [TukeyHSD](#)

Examples

```
##Arousal data:
data(arousal.df)
arousal.fit = lm(arousal ~ gender * picture, data = arousal.df)
summary2way(arousal.fit)

## Butterfat data:
data("butterfat.df")
fit <- lm(log(Butterfat)~Breed+Age, data=butterfat.df)
summary2way(fit, page="nointeraction", FUN = exp)
```

summaryStats

Summary Statistics

Description

Produces a table of summary statistics for the data. If the argument `group` is missing, calculates a matrix of summary statistics for the data in `x`. If `group` is present, the elements of `group` are interpreted as group labels and the summary statistics are displayed for each group separately.

Usage

```
summaryStats(x, ...)

## Default S3 method:
summaryStats(
  x,
  group = rep("Data", length(x)),
  data.order = TRUE,
  digits = 2,
  ...
)

## S3 method for class 'formula'
summaryStats(x, data = NULL, data.order = TRUE, digits = 2, ...)

## S3 method for class 'matrix'
summaryStats(x, data.order = TRUE, digits = 2, ...)
```

Arguments

| | |
|-------------------------|---|
| <code>x</code> | either a single vector of values, or a formula of the form <code>data~group</code> , or a matrix. |
| <code>...</code> | Optional arguments which are passed to the summary statistic functions. For example <code>na.rm = TRUE</code> will help if there are missing values in the (response) variable. |
| <code>group</code> | a vector of group labels. |
| <code>data.order</code> | if TRUE, the group order is the order which the groups are first encountered in the vector 'group'. If FALSE, the order is alphabetical. |
| <code>digits</code> | the number of decimal places to display. |
| <code>data</code> | an optional data frame containing the variables in the model. |

Value

If `x` is a single variable, i.e. there are no groups, then a single list is invisibly returned with the following named items:

| | |
|-----------------------|---|
| <code>min</code> | Minimum value. |
| <code>max</code> | Maximum value. |
| <code>mean</code> | Mean value. |
| <code>var</code> | Variance – the average of the squares of the deviations of the data values from the sample mean. |
| <code>sd</code> | Standard deviation – the square root of the variance. |
| <code>n</code> | Number of data values – size of the data set. |
| <code>nMissing</code> | If there are missing values, and <code>na.rm</code> has been set to TRUE then this item will contain the number of missing values. |
| <code>iqr</code> | Midspread (IQR) – the range spanned by central half of data; the interquartile range. |
| <code>skewness</code> | Skewness statistic – indicates how skewed the data set is. Positive values indicate right-skew data. Negative values indicate left-skew data. |
| <code>lq</code> | Lower quartile |
| <code>median</code> | Median – the middle value when the batch is ordered. |
| <code>uq</code> | Upper quartile |

If grouping is provided, either by using the `group` argument, or providing a factor in a formula, or by passing a matrix where the different columns represent the groups, then the function will return a `data.frame` a row containing all the statistics above for each group.

Methods (by class)

- `summaryStats(default)`: Summary Statistics
- `summaryStats(formula)`: Summary Statistics
- `summaryStats(matrix)`: Summary Statistics

Examples

```
## STATS20x data:
data(course.df)

## Single variable summary
with(course.df, summaryStats(Exam))

## Using a formula
summaryStats(Exam ~ Stage1, course.df)

## Using a matrix
X = cbind(rnorm(50), rnorm(50))
summaryStats(X)

## Saving and extracting the information
sumStats = summaryStats(Exam ~ Degree, course.df)
sumStats

## Just the BAs
sumStats['BA', ]

## Just the means
sumStats$mean
```

teach.df

Comparison of Three Teaching Methods

Description

Data from an experiment to assess the impact of three different teaching methods on language ability. 30 students were randomly allocated into three groups, one for each method. The students' IQ before instruction and a language test score after instruction were recorded.

Format

A data frame with 30 observations on 3 variables.

| | | | |
|------|--------|---------|---------------------------------------|
| [,1] | lang | numeric | Language test score after instruction |
| [,2] | IQ | numeric | Student's IQ |
| [,3] | method | factor | Teaching method (1, 2, 3) |

| | |
|---------------|--------------------------------------|
| technitron.df | <i>Technitron Salary Information</i> |
|---------------|--------------------------------------|

Description

Salary information for all salaried employees of the Technitron Company.

Format

A data frame with 46 observations on 8 variables.

| | | | |
|------|-----------|---------|--|
| [,1] | salary | numeric | Annual Salary (dollars) |
| [,2] | yrs.empl | numeric | Number of years employed at Technitron |
| [,3] | prior.yrs | numeric | Number of years prior experience |
| [,4] | edu | numeric | Years of education after high school |
| [,5] | id | numeric | Company identification number |
| [,6] | gender | numeric | Gender (0 = female, 1 = male) |
| [,7] | dept | numeric | Department employee works in (1 = Sales, 2 = Purchasing, 3 = Advertising, 4 = Engineering) |
| [,8] | super | numeric | Number of employees supervised |

| | |
|------------|--|
| thyroid.df | <i>Effect of a New Drug on Thyroid Weights</i> |
|------------|--|

Description

Data from an experiment to assess the effect of a new drug on the weight of the thyroid gland using 16 laboratory animals. The animals were randomly assigned into either a control group, or a treatment group, and each animal had its bodyweight recorded at the beginning of the experiment and its thyroid weight measured at the end of the experiment.

Format

A data frame with 16 observations on 3 variables.

| | | | |
|------|---------|---------|--|
| [,1] | thyroid | numeric | Weight of thyroid gland after 7 days (mg) |
| [,2] | body | numeric | Animal body weight before experiment began (g) |
| [,3] | group | factor | Animal's group (1 = control, 2 = drug) |

| | |
|---------------|-------------------------|
| toothpaste.df | <i>Crest Toothpaste</i> |
|---------------|-------------------------|

Description

Two random samples of households, one of households who purchase Crest toothpaste and one of households who do not. For each household the age is recorded of the person responsible for purchasing the toothpaste.

Format

A data frame with 20 observations on 2 variables.

| | | | |
|------|---------------|---------|--|
| [,1] | purchasers | numeric | Age of the person in the household responsible for purchases of Crest |
| [,2] | nonpurchasers | numeric | Age of the person in the household responsible for purchases of other brands of toothpaste |

| | |
|--------------|-------------------------------|
| trendscatter | <i>Trend and scatter plot</i> |
|--------------|-------------------------------|

Description

Plots a scatter plot for the variables x , y along with a lowess smooth for the underlying trend. One standard deviation error bounds for the scatter about this trend are also plotted.

Usage

```
trendscatter(x, ...)

## Default S3 method:
trendscatter(x, y = NULL, f = 0.5, xlab = NULL, ylab = NULL, main = NULL, ...)

## S3 method for class 'formula'
trendscatter(
  x,
  f = 0.5,
  data = NULL,
  xlab = NULL,
  ylab = NULL,
  main = NULL,
  ...
)
```

Arguments

| | |
|------|--|
| x | the coordinates of the points in the scatter plot. Alternatively, a formula. |
| ... | Optional arguments |
| y | the y coordinates of the points in the plot, ignored if x is a function. |
| f | the smoother span. This gives the proportion of points in the plot which influence the smooth at each value. Larger values give more smoothness. |
| xlab | a title for the x axis: see title . |
| ylab | a title for the y axis: see title . |
| main | a title for the plot: see title . |
| data | an optional data frame containing the variables in the model. |

Value

Returns the plot.

Methods (by class)

- `trendscatter(default)`: Trend and scatter plot
- `trendscatter(formula)`: Trend and scatter plot

See Also

[residPlot](#)

Examples

```
# A simple polynomial
x = rnorm(100)
e = rnorm(100)
y = 2 + 3 * x - 2 * x^2 + 4 * x^3 + e
trendscatter(y ~ x)

# An exponential growth curve
e = rnorm(100, 0, 0.1)
y = exp(5 + 3 * x + e)
trendscatter(log(y) ~ x)

# Peruvian Indians data
data(peru.df)
trendscatter(BP ~ weight, data = peru.df)

# Note: this usage is deprecated
with(peru.df, trendscatter(weight, BP))
```

`zoo.df`*Zoo Attendance during an Advertising Campaign*

Description

Data for 455 days of attendance records for Auckland Zoo, from January 1, 1993. Note that only 440 values are given due to missing values. It was of interest to assess whether an advertising campaign was effective in increasing attendance.

Format

A data frame with 440 observations on 6 variables.

| | | | |
|------|---------------|---------|---|
| [,1] | attendance | numeric | Number of visitors |
| [,2] | time | numeric | Time in days since the start of the study |
| [,3] | sun.yesterday | numeric | Hours of sunshine the previous day |
| [,4] | tv.adds | numeric | Average spending on TV advertising in the previous week (1000s of dollars per day) |
| [,5] | nice.day | factor | Assessment based on number of hours of sunshine (0 = No, 1 = Yes) |
| [,6] | day.type | factor | Type of day (1 = ordinary weekday, 2 = weekend day, 3 = school holiday weekday, 4 = public holiday) |

Index

* datasets

- airpass.df, 3
- apples.df, 3
- arousal.df, 4
- beer.df, 5
- body.df, 5
- books.df, 6
- bursary.df, 7
- butterfat.df, 7
- camplake.df, 8
- chalk.df, 8
- computer.df, 10
- course.df, 11
- course2way.df, 12
- diamonds.df, 14
- fire.df, 19
- fruitfly.df, 21
- house.df, 22
- incomes.df, 22
- lakemary.df, 25
- larain.df, 25
- mazda.df, 27
- mening.df, 27
- mergers.df, 27
- mozart.df, 30
- nail.df, 31
- oysters.df, 36
- peru.df, 37
- rain.df, 41
- seeds.df, 44
- sheep.df, 45
- skulls.df, 46
- snapper.df, 46
- soyabean.df, 47
- teach.df, 53
- technitron.df, 54
- thyroid.df, 54
- toothpaste.df, 55
- zoo.df, 57

* debugging

- getVersion, 21

* device

- layout20x, 25

* hplot

- autocorPlot, 4
- boxqq, 6
- cooks20x, 10
- eovcheck, 16
- interactionPlots, 22
- modcheck, 28
- normcheck, 31
- onewayPlot, 34
- pairs20x, 36
- residPlot, 42
- stripqq, 47
- trendscatter, 55

* htest

- ciReg, 9
- crosstabs, 13
- freq1way, 19
- levene.test, 26
- multipleComp, 30
- predict20x, 37
- predictCount, 39
- predictGLM, 40
- props1sd.new, 41
- rowdistr, 43

* models

- crossFactors, 12
- estimateContrasts, 17
- rr, 44
- summary1way, 48
- summary2way, 49

* multivariate

- summaryStats, 51

* univar

- skewness, 45

- airpass.df, 3

- anova, 9, 26, 49
- aov, 49
- apples.df, 3
- arousal.df, 4
- as.data.frame, 38–40
- autocor.plot (autocorPlot), 4
- autocorPlot, 4

- beer.df, 5
- body.df, 5
- books.df, 6
- boxqq, 6
- bursary.df, 7
- butterfat.df, 7

- camplake.df, 8
- chalk.df, 8
- ciReg, 9
- computer.df, 10
- cooks20x, 10, 28
- course.df, 11
- course2way.df, 12
- crossFactors, 12, 26
- crosstabs, 13, 41, 44

- diamonds.df, 14
- displayPairs, 14
- dummy.coef, 49

- eovcheck, 16, 28
- estimateContrasts, 17

- factor, 13
- fire.df, 19
- freq1way, 19
- fruitfly.df, 21

- getVersion, 21
- glm, 39, 40

- house.df, 22

- incomes.df, 22
- interactionPlots, 22

- lakemary.df, 25
- larain.df, 25
- layout20x, 25
- levene.test, 17, 26
- lm, 9, 10, 48

- mazda.df, 27
- mening.df, 27
- mergers.df, 27
- modcheck, 28
- model.tables, 51
- modelcheck, 29
- mozart.df, 30
- multipleComp, 18, 30

- nail.df, 31
- normcheck, 28, 31

- onewayPlot, 34, 49
- oysters.df, 36

- pairs20x, 36
- par, 6, 28, 33
- peru.df, 37
- plot, 29
- predict, 38–40
- predict.glm, 39, 40
- predict.lm, 38
- predict20x, 37
- predictCount, 39, 40
- predictGLM, 40
- propplsd.new, 41

- rain.df, 41
- residPlot, 42, 56
- rowdistr, 41, 43
- rr, 44

- seeds.df, 44
- shapiro.test, 33
- sheep.df, 45
- skewness, 45
- skulls.df, 46
- snapper.df, 46
- soyabean.df, 47
- stripqq, 47
- summary, 9
- summary1way, 18, 35, 48, 51
- summary2way, 18, 24, 49, 49
- summaryStats, 51

- t.test, 35
- teach.df, 53
- technitron.df, 54
- thyroid.df, 54
- title, 16, 32, 56

toothpaste.df, [55](#)
trendscatter, [42](#), [55](#)
TukeyHSD, [57](#)
twosampPlot (onewayPlot), [34](#)
zoo.df, [57](#)